

VERDE-CAL[®]

Enhanced Calcitic Limestone

Coarse
SGN 210

GUARANTEED ANALYSIS

Total Calcium (Ca)	37%
Total Magnesium (Mg)	0.34%
Calcium Carbonate (CaCO ₃)	94%
Magnesium Carbonate (MgCO ₃)	1%
Calcium Carbonate Equivalent (CCE)	92%
Effective Neutralizing Value (ENV)	92.2%
Effective Neutralizing Power (ENP)	1847 Pounds ENP/Ton
Total Neutralizing Power (TNP)	92.7%
Relative Neutralizing Value (RNV)	92.2%
Moisture Content Does Not Exceed	0.60%
OK ECCE	92.2%
Oregon Lime Score	92.20
Florida: 1,940 lbs of product equal to one ton of standard liming material	

F1435

Derived from Calcium Carbonate

SIEVE ANALYSIS PRIOR TO PRILLING

Percent Passing 4 Mesh Sieve	100%
Percent Passing 8 Mesh Sieve	100%
Percent Passing 10 Mesh Sieve	100%
Percent Passing 20 Mesh Sieve	100%
Percent Passing 40 Mesh Sieve	100%
Percent Passing 50 Mesh Sieve	100%
Percent Passing 60 Mesh Sieve	99%
Percent Passing 100 Mesh Sieve	95%
Percent Passing 200 Mesh Sieve	90%
Meets WV Fineness classification for pulverized	

ALSO CONTAINS NON-PLANT FOOD INGREDIENTS

- 2.00% Trihydroxycarboxylic Acid (from plant extracts)
(Trihydroxycarboxylic acid as a complexing agent)
- 1.00% Alkyl Ethoxylates (200 lbs. = 1 qt.)

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.htm>

CONDITIONS OF SALE

Seller warrants that products will be labeled as required under state and federal laws and that they conform to the label description. Any non-conformance must be reported in writing to Seller within Thirty (30) days after purchase as a prerequisite to maintaining any claim against Seller. Buyer agrees to inspect all products purchased immediately upon delivery. The Seller's liability under this warranty is limited in amount to the purchase price of the product. This warranty is in lieu of all other warranties, expressed or implied, including warranties of merchantability and fitness for a particular purpose. There are no warranties which extend beyond this statement.

APPLICATION RECOMMENDATIONS

To maintain optimum pH and growing conditions, apply **VERDE-CAL** at 5 pounds per 1,000 ft² or 220 pounds per acre at least twice per growing season, or as needed. Soil test recommendations should be used to determine liming needs.

To adjust pH, apply **VERDE-CAL** at 10 pounds per 1,000 ft² or 435 pounds per acre, or as needed. In most soils this will raise the soil pH up to one full point (5.0-6.0). Retest and reapply, if needed, at this rate.

RECOMMENDED SPREADER SETTINGS (Bulk Density: 70)	APPLICATION RATE			
	5 lbs. per 1,000 ft ² (220 lbs. per acre)		10 lbs. per 1,000 ft ² (435 lbs. per acre)	
SPREADER TYPE	Setting	Width	Setting	Width
LESCO COMMERCIAL	13	10	17	10
SCOTTS ACCUPRO 2000	I	11	K	12
SCOTTS R8	O	12	S	12
LELY	8	33	9	33
VICON	24	32		
EARTHWAY	10	11	15	11
SPYKER 288	5	12	7	12
CYCLONE ROTARY	5	12	8	12

FOR INCORPORATION - AFTER APPLICATION - WET THOROUGHLY 30 MINUTES BEFORE TILLING



MADE IN USA

NET WGT. 50 LBS. (22.68 KGS.)

5484 S. Old Carriage Road, Rocky Mount, NC 27803
1-800-394-1551 • 252-937-4107 • www.aquaaid.com