

VERDE-CAL[®] G

Enhanced Gypsum

Coarse
SGN 185

GUARANTEED ANALYSIS

Calcium (Ca)	24.53%
Combined Sulfur (S)	19.60%
Calcium Sulfate (CaSO ₄)	80.00%

Derived from Gypsum

ALSO CONTAINS NON-PLANT FOOD INGREDIENTS

- 2.00% Trihydroxycarboxylic Acid (from plant extracts)
(Trihydroxycarboxylic acid as a complexing agent)
- 1.00% Alkyl Ethoxylates (200 lbs. = 1 qt.)

SIEVE ANALYSIS PRIOR TO PRILLING

100% passing	4 Mesh Sieve
98% passing	8 Mesh Sieve
97% passing	10 Mesh Sieve
90% passing	20 Mesh Sieve
75% passing	40 Mesh Sieve
67% passing	50 Mesh Sieve
60% passing	60 Mesh Sieve
50% passing	100 Mesh Sieve
40% passing	200 Mesh Sieve

F1435

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.htm>

CONDITIONS OF SALE

Seller warrants that products will be labeled as required under state and federal laws and that they conform to the label description. Any non-conformance must be reported in writing to Seller within Thirty (30) days after purchase as a prerequisite to maintaining any claim against Seller. Buyer agrees to inspect all products purchased immediately upon delivery. The Seller's liability under this warranty is limited in amount to the purchase price of the product. This warranty is in lieu of all other warranties, expressed or implied, including warranties of merchantability and fitness for a particular purpose. There are no warranties which extend beyond this statement.

APPLICATION RECOMMENDATIONS

For continued optimum growing conditions, apply **VERDE-CAL G** at 5 pounds per 1,000 ft² or 220 pounds per acre monthly through the growing season, or as needed. Soil test recommendations should be followed.

To correct high sodium or magnesium levels or to loosen clay soils, apply **VERDE-CAL G** at 10 pounds per 1,000 ft² or 435 pounds per acre once or twice per growing season, or as needed. A follow up soil test is recommended and reapply, if needed, at optimal growing condition rate.

To correct high sodium levels on Greens and Tees when using effluent water, apply **VERDE-CAL G** at 8 pounds per 1,000 ft² every month during the growing season.

RECOMMENDED SPREADER SETTINGS (Bulk Density: 70)	APPLICATION RATE			
	5 lbs. per 1,000 ft ² (220 lbs. per acre)		10 lbs. per 1,000 ft ² (435 lbs. per acre)	
SPREADER TYPE	Setting	Width	Setting	Width
LESCO COMMERCIAL	13	10	17	10
SCOTTS ACCUPRO 2000	I	11	K	12
SCOTTS R8	O	12	S	12
LELY	8	33	9	33
VICON	24	32		
EARTHWAY	10	11	15	11
SPYKER 288	5	12	7	12
CYCLONE ROTARY	5	12	8	12

WATER IN THOROUGHLY



MADE IN USA

NET WGT. 50 LBS. (22.68 KGS.)

5484 S. Old Carriage Road, Rocky Mount, NC 27803
1-800-394-1551 • 252-937-4107 • www.aquaaid.com

Revision date: 3-11-10